


SCALE 1/1

SILL TRACK TO BE SET IN HIGH QUALITY NON-SHRINK GROUT

TWO ROWS OF TYPE A ANCHOR STARTING 6" FROM THE ENDS AND SPACED 24" OC WITH ANCHOR CLUSTERS AT VERTICAL STILES (MUST USE #14 FLATHEAD ANCHORS)

ANCHOR TYPES:
 A- 1/4" STAINLESS FH TAPCON BY ITW BUILDEX WITH 1 3/4" MIN. EMBED. INTO 3000 psi CONCRETE OR BLOCK
 B- 1/4" STAINLESS FH TAPCON BY ITW BUILDEX WITH 1 1/4" MIN. EMBED. INTO PT WOOD (SG) = .55
 C- 1/4-14 SELF DRILLING GRADE 5 SCREWS INTO 1/8" METAL STRUCTURES

| | | | |
|--|------|-------------------|--------------|
|  | | | |
| <p align="center"><i>Manufacturers of Standard and Custom Sliding Doors</i></p> | | | |
| <p>1505 COMMERCE LANE, P.O. BOX 794 JUPITER, FLORIDA 33458 PHONE: (561) 746-5493</p> | | | |
| <p>DRAWING DESCRIPTION: IMPACT 3.25 TRACK CROSS SECTION</p> | | | |
| DESIGNED BY | DATE | DRAWING No. | |
| DRAWN BY | DATE | REV. | |
| APPROVED BY | DATE | AUTOCAD FILE NAME | SHEET 1 OF 1 |